

DBUS

Sources: [Wikipedia](#), [D-Bus Specification](#), [Cardinal Peak](#)

Transports

Default D-Bus message buses:

- System-wide instance / message bus (see /usr/share/dbus-1/system.conf or dbus-monitor --system)
 - User-session-specific instance / message bus (see /usr/share/dbus-1/session.conf or dbus-monitor --session)
- Monitor DBUS signals: dbus-monitor ===== DBUS
 Implementations ===== - GDBus (Gnome) - QT/KDE D-Bus - dbus-broker (Arch) =====
 Desktop Notifications ===== * Send desktop notification: notify-send test * Send desktop notification with icon: notify-send -i face-glasses "test" (icons are located in /usr/share/icons/) * Monitor DBUS desktop notifications: dbus-monitor "interface='org.freedesktop.Notifications'" =====
 Desktop Notification Daemons =====
 [[https://wiki.archlinux.org/title/Desktop_notifications|Primary source]]
 Daemons: * dunst * NotifyOSD / notify-osd Depending on the Desktop Environment, notification daemons are built-in (Cinnamon, Gnome, KDE). Notification daemons can started standalone for other environments (e.g. i3wm). Standalone is possible via XDG autostart or as DBUS service. Typically, DBUS service files are shipped with notification daemons, e.g., /usr/share/dbus-1/services/org.freedesktop.Notifications.service

From: <http://172.168.74.25/> - wiki.wurps.de

Permanent link: <http://172.168.74.25/doku.php?id=dbus&rev=1742730590>

Last update: **2025/03/23 12:49**

