

# Signal

## Signal with Proxy (Windows)

Batch file on Desktop:

[%UserProfile%\Desktop\Signal.bat](#)

```
@echo off
set HTTP_PROXY=http://<proxy>:<port>/
set HTTPS_PROXY=http://<proxy>:<port>/
start %LOCALAPPDATA%\Programs\signal-desktop\Signal.exe
```

Shortcut on Desktop with destination: C:\Windows\System32\cmd.exe /c  
"%UserProfile%\Desktop\Signal.bat"

## Signal with Proxy (Linux)

[/usr/share/applications/signal-desktop.desktop](#)

```
[Desktop Entry]
Name=Signal
Comment=Private messaging from your desktop
Exec="/opt/Signal/signal-desktop.sh" %U
Terminal=false
Type=Application
Icon=signal-desktop
StartupWMClass=Signal
Categories=Network;
desktop entry
```

[/opt/Signal/signal-desktop.sh](#)

```
#!/bin/sh

export http_proxy=http://<proxy>:<port>
export https_proxy=http://<proxy>:<port>
/opt/Signal/signal-desktop
```

From:

<http://172.168.74.25/> - **wiki.wurps.de**

Permanent link:

<http://172.168.74.25/doku.php?id=signal&rev=1540473358>

Last update: **2020/12/29 02:09**

